### A NOTE ON POINT SOURCE DIFFRACTION BY A WEDGE

A. D. RAWLINS

Received 18 June 2003

The object of this paper is to give new expressions for the wave field produced when a time harmonic point source is diffracted by a wedge with Dirichlet or Neumann boundary conditions on its faces. The representation of the total field is expressed in terms of quadratures of elementary functions, rather than Bessel functions, which is usual in the literature. An analogous expression is given for the three-dimensional free-space Green's function.

#### 1. Introduction

The wave field produced when a line or point source is diffracted by an ideal wedge was first given by Macdonald [5] following Poincaré [7] in terms of a Fourier-Bessel series some time ago. Since that time, no substantial simplification has been carried out—see Bowman et al. [1]. By using this Fourier-Bessel series, it is possible by means of an integral representation given by Lamb [4] and various results due to Macdonald [6] to produce a new representation that avoids Bessel functions completely and only involves elementary trigonometric expressions. To the author's knowledge, these results are new, although it is surprising that such results have not appeared before since the approach is quite elementary. The new representation offers a more compact representation for the total wave field that is easy to compute. A new representation is also given for a harmonic point source, that is, the three-dimensional free-space Green's function for the reduced wave equation.

#### 2. Formulation of the boundary value problem

We will assume a harmonic point wave source  $u_0e^{-iwt}$ , where *w* is the angular frequency located at cylindrical polar coordinates  $Q(r_0, \theta_0, z_0)$ , where the field at any other point  $P(r, \theta, z)$  is given by

$$u_0(r,\theta,z) = \frac{e^{ikR}}{R},\tag{2.1}$$

Copyright © 2004 Hindawi Publishing Corporation

Journal of Applied Mathematics 2004:1 (2004) 85-89

2000 Mathematics Subject Classification: 78A25, 78A30, 78A40, 78A45, 78A50, 78A55, 78A97 URL: http://dx.doi.org/10.1155/S1110757X04306066



Figure 2.1. The *z*-axis lies along the edge of the wedge. The radial distances *r* and *r*<sub>0</sub> lie in a plane perpendicular to the *z*-axis. The distance  $R = \{r^2 + r_0^2 - 2rr_0\cos(\theta - \theta_0) + (z - z_0)^2\}^{1/2}$  lies between the point *P* in the plane z = z and *Q* in the plane  $z = z_0$ .

where  $k = 2\pi/\lambda$  ( $\lambda$  is the wave length) and  $R = \{r^2 + r_0^2 - 2rr_0 \cos(\theta - \theta_0) + (z - z_0)^2\}^{1/2}$  is the distance between the source point *Q* and any other point *P*. A solid wedge is assumed to occupy the region ( $r \ge 0$ ,  $0 \le \theta \le \alpha$ ,  $-\infty < z < \infty$ ) and the source point lies in the complementary region, thus  $0 < r_0$ ,  $\alpha < \theta_0 < 2\pi$ , and  $-\infty < z_0 < \infty$ ; see Figure 2.1.

The unique solution  $u^D$  of the Dirichlet (u = 0 on  $\theta = 0$ ,  $\theta = \alpha$ ) and  $u^N$  of the Neumann ( $\partial u/\partial \theta = 0$  on  $\theta = 0$ ,  $\theta = \alpha$ ) boundary value problem that satisfies the reduced wave equation, the radiation, and edge condition, is well known, and is given by Bowman et al. [1] as

$$u^{D/N} = \frac{2\pi}{\alpha} \sum_{n=0}^{\infty} \in_n \sup_{\cos} \{ \nu_n \theta_0 \}_{\cos}^{\sin} \{ \nu_n \theta \} I_n(r, z; r_0 z_0), \qquad (2.2)$$

where

$$I_{n}(r,z;r_{0},z_{0}) = \int_{-\infty}^{\infty} J_{\nu_{n}}(hr_{<})H_{\nu_{n}}^{(1)}(hr_{>})e^{-|z-z_{0}|\sqrt{(h^{2}-k^{2})}}\frac{h\,dh}{\sqrt{(h^{2}-k^{2})}},$$
(2.3)

and  $r_{>} = r_0$ ,  $r_{<} = r$  when  $r_0 > r$ ; and  $r_{>} = r$ ,  $r_{<} = r_0$  when  $r > r_0$ , with  $v_n = n\pi/\alpha$ ,  $\epsilon_0 = 1/2$ , and  $\epsilon_n = 1$ ,  $n \ge 1$ ; and the square root is defined by

$$\sqrt{(h^2 - k^2)} = \sqrt{|h^2 - k^2|}, \quad h^2 > k^2, 
= -i\sqrt{|k^2 - h^2|}, \quad h^2 < k^2.$$
(2.4)

Although Bowman et al. [1] state that  $I_n$  cannot be simplified, we show that it can be expressed in terms of elementary functions as follows.

We can write (2.3) as

$$I_{n} = \int_{0}^{\infty} J_{\nu_{n}}(hr_{<}) H_{\nu_{n}}^{(1)}(hr_{>}) e^{-|z-z_{0}|\sqrt{(h^{2}-k^{2})}} \frac{h \, dh}{\sqrt{(h^{2}-k^{2})}} - \int_{0}^{\infty} J_{\nu_{n}}(-hr_{<}) H_{\nu_{n}}^{(1)}(-hr_{>}) e^{-|z-z_{0}|\sqrt{(h^{2}-k^{2})}} \frac{h \, dh}{\sqrt{(h^{2}-k^{2})}}.$$
(2.5)

#### A. D. Rawlins 87

And by using the fact that  $H_{\nu}^{(1)}(ze^{i\pi}) = -e^{-i\nu\pi}H_{\nu}^{(2)}(z)$  and  $J_{\nu}(ze^{i\pi}) = e^{\nu\pi i}J_{\nu}(z)$ , we get

$$I_{n} = \int_{0}^{\infty} J_{\nu_{n}}(hr_{<}) = \{H_{\nu_{n}}^{(1)}(hr_{>}) + H_{\nu_{n}}^{(2)}(hr_{<})\}e^{-|z-z_{0}|\sqrt{(h^{2}-k^{2})}}\frac{h\,dh}{\sqrt{(h^{2}-k^{2})}}$$

$$= 2\int_{0}^{\infty} J_{\nu_{n}}(hr_{<})J_{\nu_{n}}(hr_{>})e^{-|z-z_{0}|\sqrt{(h^{2}-k^{2})}}\frac{h\,dh}{\sqrt{(h^{2}-k^{2})}}.$$
(2.6)

But Lamb [4] has shown that for the root determination (2.4),

$$\frac{e^{-|z-z_0|\sqrt{(h^2-k^2)}}}{\sqrt{(h^2-k^2)}} = \int_0^\infty J_0(ht) \frac{e^{ik\sqrt{(t^2+|z-z_0|^2)}}}{\sqrt{(t^2+|z-z_0|^2)}} t \, dt.$$
(2.7)

Substituting (2.7) into (2.6) and interchanging the order of integration (permissible since the double integral is uniformly convergent before and after the interchange of order of integration), we get

$$I_n = 2 \int_0^\infty \frac{t e^{ik\sqrt{(t^2 + |z - z_0|^2)}}}{\sqrt{(t^2 + |z - z_0|^2)}} \left( \int_0^\infty h J_{\nu_n}(hr_0) J_{\nu_n}(hr) J_0(ht) dh \right) dt.$$
(2.8)

The integral in the brackets of the last expression has been evaluated by Macdonald [6] as

$$W = \int_{0}^{\infty} h J_{\nu_{n}}(hr_{0}) J_{\nu_{n}}(hr) J_{0}(ht) dh$$
  
=  $i \sqrt{\frac{2}{\pi}} \frac{\sin \nu_{n} \pi}{rr_{0} \pi} Q_{\nu_{n}-1/2}^{1/2}(\mu)(\mu) (\mu^{2}-1)^{-1/4}, \quad |t| > |r+r_{0}|, \mu > 1$   
=  $\frac{1}{\sqrt{2\pi}} \frac{1}{rr_{0}} (1-\mu^{2})^{-1/4} P_{\nu_{n-1/2}}^{1/2}(-\mu), \quad |r+r_{0}| > |t| > |r-r_{0}|, -1 < \mu < 1$   
=  $0, \quad |r-r_{0}| > |t|,$  (2.9)

where  $-\mu = (r^2 + r_0^2 - t^2)/2rr_0$ .

But the associated Legendre functions  $P_{\nu_n-1/2}^{1/2}(-\mu)$  and  $Q_{\nu_n-1/2}^{1/2}(\mu)$  can be represented in terms of elementary functions by explicit evaluation of the integrals given in Hobson [3, (90), page 244 and (91), page 245]:

$$(1-\mu^2)^{1/4} P_{\nu_n-1/2}^{1/2}(-\mu) = \sqrt{\frac{\pi}{2}} \cos\left(\nu_n \cos^{-1}(-\mu)\right), \quad -1 < \mu < 1,$$
  
$$(\mu^2 - 1)^{1/4} Q_{\nu_n-1/2}^{1/2}(\mu) = i \sqrt{\frac{2}{\pi}} e^{-\nu_n \cosh^{-1}(\mu)}, \quad \mu > 1.$$
 (2.10)

Thus

$$W = \begin{cases} -\frac{2}{\pi} \frac{\sin v_n \pi}{\pi r r_0} \frac{e^{-v_n \cosh^{-1} \mu}}{(\mu^2 - 1)^{1/2}}, & |t| > |r + r_0|, \mu > 1, \\ \frac{1}{2r r_0} \frac{\cos (v_n \cos^{-1} (-\mu))}{(1 - \mu^2)^{1/2}}, & |r + r_0| > |t| > |r - r_0|, \\ 0, & |r - r_0| > |t|. \end{cases}$$
(2.11)

#### 88 A note on point source diffraction by a wedge

Hence, substituting (2.11) into (2.8) gives

$$I_{n} = \frac{1}{rr_{0}} \int_{|r-r_{0}|}^{|r+r_{0}|} \frac{\cos\left(\nu_{n}\cos^{-1}\mu\right)te^{ik\sqrt{(t^{2}+|z-z_{0}|^{2})}}dt}{\left(1-\mu^{2}\right)^{1/2}\sqrt{\left(t^{2}+|z-z_{0}|^{2}\right)}} - \frac{4\sin\nu_{n}\pi}{\pi^{2}rr_{0}} \int_{|r+r_{0}|}^{\infty} \frac{e^{-\nu_{n}\cosh^{-1}\mu}}{\left(\mu^{2}-1\right)^{1/2}} \frac{e^{ik\sqrt{(t^{2}+|z-z_{0}|^{2})}}}{\sqrt{\left(t^{2}+|z-z_{0}|^{2}\right)}}tdt.$$
(2.12)

Thus we have reduced the evaluation of (2.3) to that of (2.12) which can be seen to be more suitable for rapid numerical computation since it does not involve Bessel functions.

#### 3. Free-space Green's function

It is well known from Duffy [2, (5.1.67), page 285] that

$$\frac{e^{ikR}}{R} = \sum_{n=-\infty} g_n(r,z;r_0,z_0) \cos n(\theta - \theta_0), \qquad (3.1)$$

where  $g_n(r,z;r_0,z_0) = \int_0^\infty h J_n(rh) J_n(r_0h) e^{-|z-z_0|\sqrt{(h^2-k^2)}} (dh/\sqrt{(h^2-k^2)})$ . By using Lambs expression (2.7) with the root determination (2.4), we get

$$g_n(r,z;r_0,z_0) = \int_0^\infty \frac{te^{ik\sqrt{(t^2+|z-z_0|^2)}}}{\sqrt{(t^2+|z-z_0|)^2}} \left(\int_0^\infty h J_n(rh) J_n(r_0h) J_0(ht) dh\right) dt.$$
(3.2)

Now by using (2.9), and remembering that *n* is an integer, we get

$$g_{n}(r,z;r_{0},z_{0}) = \frac{1}{2\pi r r_{0}} \int_{|r-r_{0}|}^{|r+r_{0}|} \frac{e^{ik\sqrt{(t^{2}-|z-z_{0}|^{2})}}}{\sqrt{(t^{2}+|z-z_{0}|)^{2}}} \frac{P_{n-1/2}^{1/2}(-\mu)}{(1-\mu^{2})^{1/4}} t dt$$

$$= \frac{1}{2r r_{0}} \int_{|r-r_{0}|}^{|r+r_{0}|} \frac{e^{ik\sqrt{(t^{2}-|z-z_{0}|^{2})}}}{\sqrt{(t^{2}+|z-z_{0}|^{2})}} \frac{\cos(n\cos^{-1}(-\mu))}{(1-\mu^{2})^{1/2}} t dt.$$
(3.3)

So we have the free-space Green's function representation

$$\frac{e^{ikR}}{R} = \frac{1}{2rr_0} \sum_{n=-\infty}^{\infty} \cos n(\theta - \theta_0) \left\{ \int_{|r-r_0|}^{|r+r_0|} \frac{e^{ik\sqrt{(t^2 - |z-z_0|^2)}}}{\sqrt{\left(t^2 + |z-z_0|^2\right)}} \frac{\cos^{-1}(n\cos\mu)}{\left(1-\mu^2\right)^{1/2}} t \, dt \right\}, \quad (3.4)$$

which to my knowledge is a new representation.

Finally, in conclusion, we have derived new representations for the harmonic Green's function for a wedge with Dirichlet or Neumann boundary conditions on its faces. We have also derived a new expression for the three-dimensional free-space Green's function. It is surprising that neither Lamb nor Macdonald discovered these results since the basis of the results exists in the two papers by Lamb [4] and Macdonald [6] that were published consecutively in the same journal.

#### References

- [1] J. J. Bowman, T. B. A. Senior, and P. L. E. Uslenghi, *Electromagnetic and Acoustic Scattering by Simple Shapes*, North Holland Publishing, Amsterdam, 1969, Chapter 6.
- [2] D. G. Duffy, *Green's Functions with Applications*, Studies in Advanced Mathematics, Chapman & Hall/CRC, Florida, 2001.
- [3] E. W. Hobson, *The Theory of Spherical and Ellipsoidal Harmonics*, Cambridge University Press, Cambridge, 1931.
- [4] H. Lamb, On the theory of waves propagated vertically in the atmosphere, Proc. London Math. Soc. (2) 7 (1909), 122–141.
- [5] H. M. Macdonald, *Electric Waves*, Cambridge University Press, Cambridge, 1902.
- [6] \_\_\_\_\_, Note on the evaluation of a certain integral containing Bessel's functions, Proc. Lon. Math. Soc. (2) 7 (1909), 142–149.
- [7] H. Poincaré, Sur la polarisation par diffraction, Acta Math. 16 (1892), 297–339 (French).

A. D. Rawlins: Department of Mathematical Sciences, Brunel University, Uxbridge, Middlesex UB8 3PH, UK

E-mail address: anthony.rawlins@brunel.ac.uk

# Special Issue on Decision Support for Intermodal Transport

## **Call for Papers**

Intermodal transport refers to the movement of goods in a single loading unit which uses successive various modes of transport (road, rail, water) without handling the goods during mode transfers. Intermodal transport has become an important policy issue, mainly because it is considered to be one of the means to lower the congestion caused by single-mode road transport and to be more environmentally friendly than the single-mode road transport. Both considerations have been followed by an increase in attention toward intermodal freight transportation research.

Various intermodal freight transport decision problems are in demand of mathematical models of supporting them. As the intermodal transport system is more complex than a single-mode system, this fact offers interesting and challenging opportunities to modelers in applied mathematics. This special issue aims to fill in some gaps in the research agenda of decision-making in intermodal transport.

The mathematical models may be of the optimization type or of the evaluation type to gain an insight in intermodal operations. The mathematical models aim to support decisions on the strategic, tactical, and operational levels. The decision-makers belong to the various players in the intermodal transport world, namely, drayage operators, terminal operators, network operators, or intermodal operators.

Topics of relevance to this type of decision-making both in time horizon as in terms of operators are:

- Intermodal terminal design
- Infrastructure network configuration
- Location of terminals
- Cooperation between drayage companies
- Allocation of shippers/receivers to a terminal
- Pricing strategies
- Capacity levels of equipment and labour
- Operational routines and lay-out structure
- Redistribution of load units, railcars, barges, and so forth
- Scheduling of trips or jobs
- Allocation of capacity to jobs
- Loading orders
- Selection of routing and service

Before submission authors should carefully read over the journal's Author Guidelines, which are located at http://www .hindawi.com/journals/jamds/guidelines.html. Prospective authors should submit an electronic copy of their complete manuscript through the journal Manuscript Tracking System at http://mts.hindawi.com/, according to the following timetable:

Manuscript Due	June 1, 2009
First Round of Reviews	September 1, 2009
Publication Date	December 1, 2009

#### **Lead Guest Editor**

**Gerrit K. Janssens,** Transportation Research Institute (IMOB), Hasselt University, Agoralaan, Building D, 3590 Diepenbeek (Hasselt), Belgium; Gerrit.Janssens@uhasselt.be

#### **Guest Editor**

**Cathy Macharis,** Department of Mathematics, Operational Research, Statistics and Information for Systems (MOSI), Transport and Logistics Research Group, Management School, Vrije Universiteit Brussel, Pleinlaan 2, 1050 Brussel, Belgium; Cathy.Macharis@vub.ac.be

Hindawi Publishing Corporation http://www.hindawi.com